

ADC THEATRE – LARKUM STUDIO

TECHNICAL SPECIFICATION

Room layout

Maximum capacity 40 seated, 60 standing depending on staging requirements.

Hardwood sprung floor, in natural colour.

White painted walls with black surge curtains which can be extended around the entire room.

Overhead grid at approx. 3m height containing projector and projection screen, as well as hard-wired lighting bars.

Dressing Rooms & Green room

Two dressing rooms (accommodating 25-30). Sewing machine, Iron, Ironing board, washing and tumble drying facilities.

Green room with seating and coke machine. Dressing room facilities are shared with the productions using the main auditorium.

Workshop & Set Construction

Small Workshop with Radial Arm Saw, Circular Saw, Mortising Machine, Cutoff Saw, Panel Saw, various drills, jigsaws and hand tools. Scene dock for small-scale set building, with electric hoist to raise larger set pieces to stage. Workshop facilities are shared with productions using the main auditorium.

Stage Management

Control position next to Front of House entrance to Studio, with paging controls, phone, fire alarm repeater and all sound and lighting controls. Techpro intercom system with optional link to main stage ring, and points around room.

Lighting

Control by Zero88 Jester 24/48 lighting desk. 24 channels of dimming (Zero88 Chilli Pro), hard wired around studio (18 high level and 6 at floor level).

Fixed rig of 2x Source4 Junior, 2x CCT Minulette Pro Reflector and 4x CCT Minulette Fresnel. Other lanterns may be available from main theatre stock - see lighting stock list for details of lanterns and accessories, and discuss your requirements with the Production Manager.

Sound

Control by Allen & Heath GR05 mixer. Output to 4 JBL Control 45 speakers around room (individually controllable) and JBL Sub. CD player and stereo 3.5mm jack inputs available. Audio and video links to far ends of room, patchable in rack.

See sound stock list for details of microphones and accessories available.

Musical Equipment

1 baby grand which may be removed for performances at cost.