

Standard Frontwash

What is in the Standard Frontwash?

The standard lighting rig includes the following lanterns at the following positions:

- **Bridge 1:** 6x RJ 613 – Midstage frontwash
- **Bridge 2:** 6x RJ 614 – Forestage frontwash

You are welcome to derig these lights and use a different frontwash. If so you may store the 3 RJs at the end of each bridge (for a total of 6 per bridge, plus two followspots on bridge 2). All must have their secondary chain attached around the railing at the rear of the bridge.

How should a rig look after the get-out?

The 6x RJ 613 and 6x RJ 614 should be present on bridges 1 and 2 respectively. They do not need to be rigged or patched. The followspots should be left at either end of Bridge 2.

Any other lights on the bridges should be derigged and returned to the OP Quad (if conventional), or the side of stage (if LED). All lanterns over stage should be derigged.

Lanterns may be left rigged, both on the bridges and overstage, at the discretion of the incoming show – please coordinate with their lighting designer to see what can be kept.

All derigged lanterns should be stored as follows:

Lantern Type	Storage Location
Standard Frontwash	
6x RJ 613	Ends of Bridge 1
6x RJ 614	Ends of Bridge 2
Conventionals	
Conventional lanterns	OP Quad
Overflow Parcans	Upstage Winch
Birdies	Step Bins
Intelligent Fixtures	
Colorsource PARs	OP Quad
ETC Source 4 LED Lustr S2	OP Side of Stage
Altman Spectra CYC 200	Hooks on back wall of stage
RJ Roxie Followspots	Ends of Bridge 2
Strobes	Step Bins